

Teksan Co.

Light Spectroscopy Instruments

Address

Unit 104, Technology Units
Incubator, Shahid Beheshti
University, Tehran, Iran
Postal code: 1983969411

Contact information

Tel: +98 21 22402199
Telegram: @Teksanco
Fax: +98 21 43855749
[Linkedin.com/company/Teksan-co/](https://www.linkedin.com/company/Teksan-co/)

Website and E-mail

www.teksan.ir
Sales@teksan.ir
info@teksan.ir

For more information on any of
our products or services please
visit us on the Web.

LENA Double Beam Spectrophotometer

High Resolution Low-Noise Spectrophotometer for Sensitive Application

Full option and user-friendly computer program



Application Areas

- Engineering
- Food & Beverage Quality Control
- Chemistry
- Laser Characterization
- Biology
- Physics & Astronomy
- Protein & Nucleic Acid Analysis
- Volcanology
- Color Analysis
- Environments
- Nanotechnology
- Polymers

Spectrophotometry is a method to measure how much a chemical substance absorbs light by measuring the intensity of light as a beam of light passes through sample solution.

UV-Visible and NIR spectroscopy is a mature and well-established analytical technique used extensively in many industry sectors including Environmental Analysis, Pharmaceutical Testing, Food and Beverage Production to name but a few. Teksan manufactures an extensive range of UV and Visible and NIR Spectroscopy instrumentation guaranteed to meet the needs of your application. Further information on the UV-Vis-NIR product line along with a brief introduction to UV-Spectroscopy can be found in our website.

- High performance
- Low stray light
- High Wavelength accuracy
- blazed grating 300-600-1200lines/mm.
- Local control software for photometric fixed wavelength measurement.
- Easily upgraded to include quantitative analysis, multi wavelength spectrum & kinetics.
- Easy to use cell holder storage.
- Robust modular design with a small footprint.
- Can be used with WIN-Linux-MAC software.

Teksan Co.

Light Spectroscopy Instruments

Address

Unit 104, Technology Units
Incubator, Shahid Beheshti
University, Tehran, Iran
Postal code: 1983969411

Contact information

Tel: +98 21 22402199
Telegram: @Teksanco
Fax: +98 21 43855749
[Linkedin.com/company/Teksan-co/](https://www.linkedin.com/company/Teksan-co/)

Website and E-mail

www.teksan.ir
Sales@teksan.ir
info@teksan.ir

For more information on any of
our products or services please
visit us on the Web.

Features and Specifications

Optical Specifications	
Mode	Double Beam Configuration
Detection	array detector
Wavelength Range	200-950 nm
Optical Resolution	1.7 nm (Configuration dependent)
Light Source	Deuterium & Tungsten halogen lamp
Absorbance	0 to 3.5 A
Stray Light	<0.03 %T
Wavelength Accuracy	<±0.1 nm
Wavelength Reproducibility	< ±0.02 nm
Photometric Accuracy	Using potassium dichromate, EP method < ± 0.01 A
Photometric Noise (RMS)	< 0.001 A 60 scan at 0 A, 500 nm
Photometric Stability	<0.002 A/h after 1 hr. warm-up
Baseline Flatness (RMS)	<0.01 A - 0.5 sec blank, 0.5 sec scan
Scan Time	0.5 ms to 10 s
Typical Scan Time	20 ms
Software and System	
Software	Tunsu
Operational System	Windows-Linux-MAC
Physical Dimensions (NO Hard case)	
Size (W x D x H)	490 x 417 x 258 mm
Weight	15kg
Physical Dimensions (With Hard case)	
Size (W x D x H)	590 x 517 x 358 mm
Weight	19kg
Power Requirements	
Power Consumption	100 W
Line Voltage	220 V
Line Frequency	50-60 Hz
Environmental Conditions	
Operating Temperature	5 – 35 °C
Non-Operating Temperature	-20 – 50 °C
Humidity	<95% @ 20-40 °C

SERVICES AVAILABLE

Technical Support
Installation and Setup
Maintenance
Application Support
Hardware Support
Guaranteed Warranty