

Teksan Co.

Light Spectroscopy Instruments

Address

Unit 104, Technology Units Incubator, Shahid Beheshti University, Tehran, Iran Postal code: 1983969411

Contact information

Tel: +98 21 22402199 Telegram: @Teksanco Fax: +98 21 43855749 Linkedin.com/company/Teksan-co/

Website and E-mail

www.teksan.ir Sales@teksan.ir info@teksan.ir

For more information on any of our products or services please visit us on the Web.

TIDA Low Noise Spectrometer (200-850)

High Resolution Low-Noise Cooled Spectrometer for Sensitive Application

Full option and user-friendly computer program



TIDA is a small-footprint, high-resolution spectrometer that is well suited for applications such as wavelength characterization of lasers and LEDs, monitoring of gases and monochromatic light sources, and determination of elemental atomic emission lines, Chemicals absorption, and color analysis, depending on spectrometer configuration, optical resolution as fine as ~0.02 nm (FWHM) is possible. Also, users can add TIDA accessories such as light sources, probes and optical fibers to configure a variety of application-specific systems. TIDA draws power from the both power supply and also host PC, eliminating the need for an external power supply.

Application Areas

- Engineering
- Food & Beverage Quality Control
- Chemistry
- Laser Characterization
- Biology
 - Physics & Astronomy
- Protein & Nucleic Acid Analysis
- Volcanology
- Color Analysis
- Environments
- Nanotechnology
- Polymers

TIDA is perfect for applications where fast reactions need to be monitored and high resolution is necessary, such as chemistry and biochemistry applications. Data programmed into a memory chip on each TIDA includes wavelength calibration coefficients, linearity coefficients, and the serial number unique to each spectrometer. Our spectrometer operating software simply reads these values from the spectrometer. a feature that enables hot swapping of spectrometers among PCs. TIDA Spectrometer connects to a notebook or desktop PC via USB port.





Teksan Co.

Light Spectroscopy Instruments

Address

Unit 104, Technology Units Incubator, Shahid Beheshti University, Tehran, Iran Postal code: 1983969411

Contact information

Tel: +98 21 22402199 Telegram: @Teksanco Fax: +98 21 43855749 Linkedin.com/company/Teksan-co/

Website and E-mail

www.teksan.ir Sales@teksan.ir info@teksan.ir

For more information on any of our products or services please visit us on the Web.

Features and Specifications

Engineering Specifications	TIDA UCS-G400 Series
PHYSICAL	
Dimensions:	171x 135 x 65 mm
(L x W x H) mm	
Weight: kg	0.75 kg
DETECTOR	
Туре:	array detector
A/D Type	16bit
Cooling	Up to -5° C
Range:	200-850 nm
SPECTROSCOPIC	
Wavelength range:	200-850 nm
Integration time:	1 microsecond – 65 seconds to 60 Min
Dynamic range:	2.5×10^8 (system); 1500:1 for a single acquisition
Signal-to-noise ratio:	1:300 up to 1:700
Dynamic Range	1300:1 for a single acquisition, 8.5 x 10^7
Low Dark Level	Yes
Low Dark Noise	Yes
Grating:	300 Line per mm
Slit:	25µm wide slits
Optical resolution:	~1.2-1.8 nm (FWHM)
Stray light:	<0.04% at 532 nm; <0.11% at 452 nm
Buffering:	No
Fiber optic connector:	SMA 905 to single-strand optical fiber (0.22 NA)
ELECTRONICS	
Power consumption:	200 mA at +5 VDC
TRIG	No
Interfaces:	USB 2.0 USB 3.0
Temperature Storage	-33° to +75° C
Temperature Operation	-15° to +50° C
Humidity:	0% – 90% non-condensing

SERVICES AVAILABLE

Technical Support Installation and Setup Maintenance Application Support Hardware Support Guaranteed Warranty

